

2022 · 2023

Product Selection Guide

「2022-2023A」

深圳顺络电子股份有限公司
Shenzhen Sunlord Electronics Co., Ltd.

Sunlord
expert in e components

深圳顺络电子股份有限公司
Shenzhen Sunlord Electronics Co., Ltd.
中国深圳市龙华新区观澜路观澜大富苑顺络工业园
Sunlord Industrial Park, Guanlan Da Fu Yuan,
Guanguang Road, Longhua, Shenzhen, China
Tel: 86-755-2983 2380 2983 2660
Fax: 86-755-8226 9029
E-mail: sunlord@sunlordinc.com



EMC componets

CHIP BEAD

for Low Speed Signal Line

GZ Series



Z@100MHz (Ω)

GZ0603	GZ1005	GZ1608	GZ2012	GZ3216
5-1000	0-1800	0-2500	0-2500	0-1200

for High Speed Signal Line

SZ Series



Z@100MHz (Ω)

SZ0603	SZ1005	SZ1608	SZ2012
5-120	0-1800	0-2700	0-2700

for Power Line

PZ Series



Z@100MHz (Ω)

Rated Current (A)

PZ0603	PZ1005	PZ1608	PZ2012	PZ3216	PZ4516
5-1000	0-600	0-600	30-600	0-1000	60-1000
0.2-1	0.45-1.8	0.5-3.0	0.8-4.0	0.5-6.0	1.5-6.0

UPZ Series



Z@100MHz (Ω)

Rated Current (A)

NEW

UPZ0603	UPZ1005	UPZ1608	UPZ2012
22-80	0-220	22-600	22-1000
1.0-1.8	0.9-2.2	1.0-6.0	1.5-6.0

EPZ Series



Z@100MHz (Ω)

Rated Current (A)

EPZ1005-4030
10-220
1.2-10.0

for High Frequency Noise Suppression

HZ Series



Z@100MHz (Ω)

NEW

HZ0603	HZ1005	HZ1608
120-600	120-1800	180-1000

HPZ Series



Z@100MHz (Ω)

Rated Current (A)

NEW

HPZ0603	HPZ1005	HPZ1608
25-50	120-220	100-1500
0.4-0.6	0.5-1.1	0.15-2.0

for Audio line

MZAS Series



Z@100MHz (Ω)

Rated Current (A)

MZAS1005	MZAS1608	MZAS2016	MZAS3225
70-1000	60-700	400	20-680
0.23-0.90	0.8-1.3	2	4-10

MZAH Series



Z@100MHz (Ω)

Rated Current (A)

MZAH1005	MZAH1608
100-4600	470
0.27-1.1	1.6

Wire Wound Ferrite Bead

WHZ Series

NEW

Inductance(nH)

Rated Current (A)

WHZ1005	WHZ1608
20-560	47-22000
0.2-1.6	0.13-1.4

COMMON MODE FILTER

for USB 2.0, C-PHY, LVDS, MIPI

SDMM-H Series

Multilayer



Common Mode Z@100MHz (Ω)

SDMM 0605H	SDMM 0906H
90	30

SDCW Series

Wire Wound



Common Mode Z@100MHz (Ω)

SDCW 1210S	SDCW 1608S	SDCW 2012C	SDCW 2012	SDCW 2520S	SDCW 3216	SDCW 3225S	SDCW 4532S
20-360	25-220	67-180	30-1000	300-1000	90-2200	80-1000	330-1400

for HDMI

SDCW-H Series

Wire Wound



Common Mode Z@100MHz (Ω)

SDCW 1210H	SDCW 2012H	SDCW 2012CH
35-90	67-120	67-120

for USB3.0

SDCW-U Series

Wire Wound



Common Mode Z@100MHz (Ω)

SDCW 1210U	SDCW 2012U
14-90	90

SDMM-U Series

Multilayer



Common Mode Z@100MHz (Ω)

NEW

SDMM 0605U	SDMM 0806U
12-25	12-90

MULTILAYER VARISTOR

for ESD Protection

SDV Series



MAX.Continuous DC Working Voltage (V)
C@ 0.5Vrms, 1MHz (pF)



SDV1005
5.5-26
0.5-80



SDV1608
5.5-48
0.5-360



SDV2012
5.5-30
18-1200

for Over-voltage Protection

SDVL-HS Series NEW



MAX.Continuous DC Working Voltage (V)
Peak Current 8/20us (A)



SDVL1608-HS
9-100
20-100



SDVL2016-HS
9-150
100-400



SDVL3216-HS
9-100
150-500



SDVL3225-HS
9-100
200-1200



MAX.Continuous DC Working Voltage (V)
Peak Current 8/20us (A)

SDVL4532-HS
9-150
500-3000



SDVL5650-HS
9-150
800-8000

SVMH Series



MAX.Continuous AC Working Voltage (V)
Peak Current 8/20us (A)



SVMH2016KA
150-320
50-180



SVMH3216KA
150-320
60-300



SVMH3225KA
150-320
150-400



SVMH4532KA
175-320
250-800

CAPACITOR

Tantalum Capacitor

TC2 Series MnO₂ Tantalum Capacitor



TC211A/B/C/D/E
(for Industry)



TC212A/B/C/D/E
(Low ESR)

Rated Voltage (V)
Capacitance (uF)
ESR (Ω)

2.5-50
0.15-680
0.4-18

2.5-50
0.15-680
0.12-15

TC3 Series Polymer Tantalum Capacitor



TC311B/C/D/E/W/G2



TC312B/C/D/E/W/G2
(High Rated Voltage)

Rated Voltage (V)
Capacitance (uF)
ESR (Ω)

2.5-16
10-1000
0.07-0.35

20-100
3.3-330
0.07-0.5

Thermistor

MULTILAYER NTC THERMISTOR

Temperature Sensing NTC

SDNT Series



SDNT0603
10-100



SDNT1005
6.8-220



SDNT1608
2.2-220



SDNT2012
4.7-220

Resistance @25 (kΩ)
25 /50 B Constant (K)

3380-4250

3380-4250

3380-4300

3450-4300



Coils/Inductors

FOR HIGH FREQUENCY

Multilayer	SDCL Series Ceramic <table border="1"> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (nH)</td> <td>0.2-33</td> <td>0.6-120</td> <td>0.6-360</td> <td>1.0-680</td> </tr> <tr> <td>Rated Current (mA)</td> <td>90-320</td> <td>80-850</td> <td>50-800</td> <td>100-500</td> </tr> </table>						Inductance (nH)	0.2-33	0.6-120	0.6-360	1.0-680	Rated Current (mA)	90-320	80-850	50-800	100-500						
Inductance (nH)	0.2-33	0.6-120	0.6-360	1.0-680																		
Rated Current (mA)	90-320	80-850	50-800	100-500																		
Multilayer	SDHL Series Ceramic High Frequency <table border="1"> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (nH)</td> <td>1.0-100</td> <td>10-180</td> </tr> <tr> <td>Rated Current (mA)</td> <td>100-500</td> <td>150-500</td> </tr> </table>				Inductance (nH)	1.0-100	10-180	Rated Current (mA)	100-500	150-500												
Inductance (nH)	1.0-100	10-180																				
Rated Current (mA)	100-500	150-500																				
Multilayer	HQ Series Ceramic High Q <table border="1"> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (nH)</td> <td>0.3-10</td> <td>0.2-56</td> <td>0.2-33</td> <td>0.6-150</td> <td>0.6-47</td> <td>0.2-20</td> </tr> <tr> <td>Rated Current (mA)</td> <td>130-650</td> <td>100-1000</td> <td>120-990</td> <td>80-1100</td> <td>130-1000</td> <td>140-990</td> </tr> </table>								Inductance (nH)	0.3-10	0.2-56	0.2-33	0.6-150	0.6-47	0.2-20	Rated Current (mA)	130-650	100-1000	120-990	80-1100	130-1000	140-990
Inductance (nH)	0.3-10	0.2-56	0.2-33	0.6-150	0.6-47	0.2-20																
Rated Current (mA)	130-650	100-1000	120-990	80-1100	130-1000	140-990																
Wire Wound	MWSD-C Series Ceramic High Q <table border="1"> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (nH)</td> <td>1.0-15</td> <td>0.8-56</td> <td>0.8-270</td> <td>1.0-51</td> <td>56-220</td> <td>3.3-560</td> </tr> <tr> <td>Rated Current (mA)</td> <td>230-900</td> <td>130-1800</td> <td>100-1000</td> <td>360-2300</td> <td>160-360</td> <td>70-850</td> </tr> </table>								Inductance (nH)	1.0-15	0.8-56	0.8-270	1.0-51	56-220	3.3-560	Rated Current (mA)	230-900	130-1800	100-1000	360-2300	160-360	70-850
Inductance (nH)	1.0-15	0.8-56	0.8-270	1.0-51	56-220	3.3-560																
Rated Current (mA)	230-900	130-1800	100-1000	360-2300	160-360	70-850																
Wire Wound	SDWL-C Series Ceramic High Q <table border="1"> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (nH)</td> <td>2.2-4700</td> <td>3.6-22000</td> <td>3.3-1200</td> <td>3.9-22000</td> <td>24-33000</td> </tr> <tr> <td>Rated Current (mA)</td> <td>30-600</td> <td>70-1000</td> <td>300-1000</td> <td>100-1000</td> <td>145-1000</td> </tr> </table>							Inductance (nH)	2.2-4700	3.6-22000	3.3-1200	3.9-22000	24-33000	Rated Current (mA)	30-600	70-1000	300-1000	100-1000	145-1000			
Inductance (nH)	2.2-4700	3.6-22000	3.3-1200	3.9-22000	24-33000																	
Rated Current (mA)	30-600	70-1000	300-1000	100-1000	145-1000																	
Wire Wound	SDWL-CP Series Ceramic High Q and Large Current <table border="1"> <tr> <td></td> <td></td> </tr> <tr> <td>Inductance (nH)</td> <td>2.6-820</td> </tr> <tr> <td>Rated Current (mA)</td> <td>180-2000</td> </tr> </table>			Inductance (nH)	2.6-820	Rated Current (mA)	180-2000															
Inductance (nH)	2.6-820																					
Rated Current (mA)	180-2000																					

FOR SIGNAL LINE

Multilayer	SDFL Series Ferrite <table border="1"> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (μH)</td> <td>0.047-3.3</td> <td>0.047-33</td> <td>0.047-47</td> <td>0.047-47</td> </tr> <tr> <td>Rated Current (mA)</td> <td>10-25</td> <td>1-50</td> <td>4-300</td> <td>5-300</td> </tr> </table>						Inductance (μH)	0.047-3.3	0.047-33	0.047-47	0.047-47	Rated Current (mA)	10-25	1-50	4-300	5-300						
Inductance (μH)	0.047-3.3	0.047-33	0.047-47	0.047-47																		
Rated Current (mA)	10-25	1-50	4-300	5-300																		
Multilayer for NFC	MCL-N Series Ferrite <table border="1"> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (μH)</td> <td>0.077-0.56</td> <td>0.077-0.82</td> </tr> <tr> <td>Rated Current (mA)</td> <td>250-550</td> <td>300-1100</td> </tr> </table>				Inductance (μH)	0.077-0.56	0.077-0.82	Rated Current (mA)	250-550	300-1100												
Inductance (μH)	0.077-0.56	0.077-0.82																				
Rated Current (mA)	250-550	300-1100																				
Wire Wound	MWSD-F Series NEW Ferrite <table border="1"> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (μH)</td> <td>0.033-0.2</td> <td>0.027-0.56</td> <td>0.018-2.2</td> <td>0.0049-47</td> <td>1.0-47</td> <td>2.2-100</td> </tr> <tr> <td>Rated Current (mA)</td> <td>110-340</td> <td>90-480</td> <td>170-2200</td> <td>50-2600</td> <td>100-700</td> <td>180-1040</td> </tr> </table>								Inductance (μH)	0.033-0.2	0.027-0.56	0.018-2.2	0.0049-47	1.0-47	2.2-100	Rated Current (mA)	110-340	90-480	170-2200	50-2600	100-700	180-1040
Inductance (μH)	0.033-0.2	0.027-0.56	0.018-2.2	0.0049-47	1.0-47	2.2-100																
Rated Current (mA)	110-340	90-480	170-2200	50-2600	100-700	180-1040																
Wire Wound	SDWL-FW Series Ferrite <table border="1"> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (μH)</td> <td>0.27-68</td> <td>0.33-10</td> <td>1.5-18</td> <td>0.12-12</td> </tr> <tr> <td>Rated Current (mA)</td> <td>40-350</td> <td>300-700</td> <td>130-320</td> <td>140-450</td> </tr> </table>						Inductance (μH)	0.27-68	0.33-10	1.5-18	0.12-12	Rated Current (mA)	40-350	300-700	130-320	140-450						
Inductance (μH)	0.27-68	0.33-10	1.5-18	0.12-12																		
Rated Current (mA)	40-350	300-700	130-320	140-450																		
Wire Wound (Resin Molded)	SDWL-F Series Ferrite <table border="1"> <tr> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Inductance (μH)</td> <td>0.01-100</td> <td>0.01-470</td> <td>0.1-1000</td> </tr> <tr> <td>Rated Current (mA)</td> <td>60-530</td> <td>25-450</td> <td>30-800</td> </tr> </table>					Inductance (μH)	0.01-100	0.01-470	0.1-1000	Rated Current (mA)	60-530	25-450	30-800									
Inductance (μH)	0.01-100	0.01-470	0.1-1000																			
Rated Current (mA)	60-530	25-450	30-800																			





Coils/Inductors

FOR POWER LINE

Multilayer

MCL Series

Magnetic Shielded

		
	MCL1608	MCL2012
Inductance (μH)	0.1-10	0.1-10
Rated Current (mA)	50-700	60-1000

Multilayer

MCL-A Series






Magnetic Shielded

			
	MCL2012A	MCL2016A	MCL2520A
Inductance (μH)	1.0-10	1.0-4.7	1.0-4.7
Rated Current (mA)	150-450	100-900	250-750

Multilayer

MPH Series

Magnetic Shielded

					
	MPH1608	MPH2012	MPH2016	MPH2520	MPHM1608
Height (mm)	0.55/0.65/0.95	0.55/0.6/0.9/1.0/1.4	1.0/1.2	1.0/1.2	0.9
Inductance (μH)	0.22-10	0.22-10	0.47-10	0.47-10	0.47-4.7
Rated Current (mA)	60-1350	110-1200	170-1350	210-1750	70-1000

Wire Wound
(Resin Molded)

SDWL-FD Series







Ferrite

			
	SDWL2520FD	SDWL3225FD	SDWL4532FD
Inductance (μH)	1.0-33	1.0-330	1.0-330
Rated Current (mA)	120-475	70-1000	90-1050

Wire Wound

SWPA Series

Magnetic Shielded
(Single Structure Type)

						
	SWPA2520	SWPA30	SWPA40	SWPA50	SWPA60	SWPA80
Height (mm)	1.0/1.2	1.0/1.2/1.5	1.0/1.2/1.8/2.0/3.0	1.2/2.0/4.0/4.5	1.2/2.0/2.8/4.5	4.0/6.0/6.5
Inductance (μH)	0.47-22	0.22-150	0.24-680	0.22-680	0.47-680	0.68-680
Rated Current (mA)	380-2350	190-3000	140-4560	250-6600	330-6500	460-7500

Wire Wound

SPH Series


Magnetic Shielded
(Low DCR)

				
	SPH2016H/U	SPH2520	SPH30	SPH40
Height (mm)	1.0	1.0/1.2	1.0/1.2/1.5	1.2/1.8
Inductance (μH)	0.05-10	0.16-82	0.22-47	0.1-330
Rated Current (mA)	450-3650	300-4050	450-3050	200-4200

Wire Wound


SWCB Series

No Magnetic Shielded

	
	SWCB1305~1807
Height (mm)	5.5~12.0
Inductance (μH)	1.0-1000
Saturation Current (mA)	500- 7100

SWCC Series



No Magnetic Shielded

	
	SWCC0603
Height (mm)	3.0
Inductance (μH)	1.0-68
Saturation Current (mA)	400- 2900

Wire Wound

SWRB Series






Magnetic Shielded
(Sleeve Type)

		
	SWRB0703-1207A	SWRB12045/055/075
Height (mm)	3.5-7.8	5.0/6.0/8.0
Inductance (μH)	1.2-680	1.0-1000
Rated Current (mA)	200-8200	480-10000

Wire Wound

SWRH Series

Magnetic Shielded
(Sleeve Type)

					
	SWRH-DR	SWRH-DS	SWRH-DC	SWRH-B	SWRH-C
Height (mm)	1.3/1.6/1.8/2.1	1.8-4.0	3.0/4.0/4.5	3.0-10	3.0/4.0/5.0
Inductance (μH)	1.2-47	1.0-1000	1.5-100	1.0-1000	1.0-820
Rated Current (mA)	140-1850	140-5200	750-6000	190-13000	230-6500





Coils/Inductors

FOR POWER LINE

Wire Wound

WPN Series

Magnetic Shielded
(Low DCR)

				
	WPN2016	WPN2520	WPN30	WPN40
Height (mm)	1.0/1.2	1.0/1.2	1.0/1.2	1.0/1.2/2.0
Inductance (μH)	0.12-10	0.16-10	0.33-15	0.22-10
Rated Current (mA)	650-5600	800-5000	1000-4200	900-8200

Wire Wound

WPG Series







Magnetic Shielded
(Low DCR)

			
	WPG2012	WPG2016	WPG2520
Height (mm)	1.0	1.0	1.0
Inductance (μH)	0.11-1.0	0.24-2.2	0.24-4.7
Rated Current (mA)	2200-5500	2150-4900	1600-5150

Wire Wound
(Molded)

WT Series NEW





Magnetic Shielded
(Large Current and Low Loss)

						
	WTX/E252012	WTX/E322512	WTH0415T	WTX0420T	WTHE0420	WTX0430T
LxWxH (mm)	2.5x2.0x1.2	3.2x2.5x1.2	4.0x4.0x1.5	4.0x4.0x2.1	4.0x4.0x2	4.0x4.0x3.1
Inductance (μH)	0.22-4.7	0.1-1	0.33-1.0	0.33-3.3	0.47-1.2	0.33-6.8
Saturation Current (A)	2-10	6.4-13	6-13	4.7-15.7	5.4-8.5	4.1-18.8

Wire Wound
(Mini Molded)

MWTC Series

Magnetic Shielded
(Small Size and Ultra Thin)

				
	MWTC1412	MWTC2012	MWTC2016	MWTC2520
LxWxH (mm)	1.4x1.2x0.65/0.8	2.0x1.2x0.8/1.0	2.0x1.6x0.8/1.0	2.5x2.0x0.8/1.0
Inductance (μH)	0.24-0.47	0.11-2.2	0.24-4.7	0.47-4.7
Saturation Current (A)	2.9-3.5	1.1-5.6	1.3-5.0	1.6-4.7

Wire Wound

WPZ Series

Magnetic Shielded
(Ultra Large Isat)

					
	WPZ04044S1	WPZ05057S1	WPZ0707	WPZ09068S1	WPZ0906A
LxWxH (mm)	4.1x4.0x4.0	5.2x5.2x6.5	7.3x6.8x3.8/4.2 7.0x7.0x5.0	9.6x6.4x8.1	9.6x(6.4,6.6)x10.1
Inductance (nH)	22-100	55-150	60-150	100-300	70-280
Saturation Current (A)	17-40	25-70	20-70	32.5-94	30-145
					
	WPZ0907	WPZ1006C	WPZ10075	WPZ1007AS1	WPZ10087
LxWxH (mm)	9.5x7.5x4.0/9.0	10.0x6.0/ 6.15x12.0	10.2/10.7x7.0x5.0 10.25x7.0x5.2	10.0x7.0x10.0	10.3x8.0x7.0 10.4x8.0x7.5
Inductance (nH)	70-300	70-330	70-30	70-330	100-330
Saturation Current (A)	26-80	30-175	19-130	37-165	28-108
					
	WPZ10088S1	WPZ11077S1	WPZ13138S1	WPZ0906/1206	WPZ10103
LxWxH (mm)	10.4x8.0x8.2	11.0x7.4x7.7	13.7x12.8x8.1	9.6x6.4x10/11.4 12.0x6.0x1.1/12.0	10.0x10.0x3.35
Inductance (nH)	80-330	70-510	110-500	70~200	100~300
Saturation Current (A)	33-130	18-150	28 -140	55~157	26~79

Coils/Inductors

TRANSFORMER

PCB Planar Transformer

TPP Series

Customized



Dimensions LxWxH (mm)	TPPED14 14x24x8.0	TPPED18 20x25x13	TPPED21 21x31x10	TPPED22 24x26x13	TPPER25 26x33x10	TPPER25 25x46x9
Power (W), Ref.	15	18	45	25	65	45
Application	AC-DC, PD	AC-DC, PD	AC-DC, PD	AC-DC, PD	AC-DC, PD	AC-DC, PD

Winding Transformer

TWS/TWP Series

Customized



Dimensions LxWxH (mm)	TWS/TWPEP07 8.0x7.0x10	TWS/TWPEP09 10x10x11	TWS/TWPEP12 16x13x11	TWS/TWPEP13 18x14x13	TWPEE16 26.5x21x12	TWPEE16 26.5x21x12
Power (W), Ref.	3	5	10	15	20	20
Application	xDSL, PoE	xDSL, PoE	xDSL, PoE	xDSL, PoE	AC-DC	AC-DC

Other Types

RTSB/TW Series

Customized

Ring Core Transformer

Pulse Transformer

Current Transformer



Dimensions LxWxH (mm)	RTSB 7 x 4 x 3	TWSHI 4.6x3.2x3.5	TWPEP05 7.0x4.5x5.5
Power (W), Ref.	< 3	30	30
Application	DC-DC	RJ45	AD-DC

WIRELESS CHARGING

Sheet

MQF Series
Ferrite Sheet

Customized



Ferrite Sheet Thickness (mm)	0.08/0.10/0.12/0.14/0.24/0.34/0.44
Application Freq. (MHz)	0.1~6.78
Magnetic Permeability (u')	150±15%/650±20%
Magnetic Permeability (u'')	5/15 Max.

Sheet

MQN Series
Crystalline Sheet

Customized



Nano Crystalline Thickness (mm)	0.02
Application Freq. (MHz)	0.1~0.2
Magnetic Permeability (u')	500±10%~1000±20%
Magnetic Permeability (u'')	40/50/70/100

NFC PRODUCT

Sheet

FS/DC Series
Ferrite Sheet

Customized



Thickness (mm)	0.04/0.06/0.08/0.10/0.12/0.14/0.19/0.30/0.40/0.50
Application Freq. (MHz)	13.56
Magnetic Permeability (u')	135/150/160
Magnetic Permeability (u'')	5

Antenna

MNFA-WFB Series
Ferrite Flexible Antenna

Customized









Thickness (mm)	0.12-0.3
Application Freq. (MHz)	13.56

RF Components





RF PRODUCT(Filter)

Multilayer Chip LC Filter

SLFB Series Band-pass

						
Center Freq. (MHz)	2450	1910-5890	2450	2450-5410	3600-4950	1920-4900

SLFL Series Low-pass





				
Cut-off Freq. (MHz)	915	787-7125	787-5500	902-5500

SLFH Series High-pass

		
Start Freq. (MHz)	5150	1358




Multilayer Chip Balun

SLBL Series Balun

				
Frequency Range (MHz)	698-2700	758-2025	699-6000	2400-8000


Multilayer Chip Diplexer

SLFD Series Diplexer

				
Frequency Range (MHz)	2400-7125	698-5950	698-5950	698-5950


Multilayer Chip Triplexer

SLFT Series Triplexer

	
Frequency Range (MHz)	1560-5950

Multilayer Coupler







SLCP Series Coupler

				
Frequency Range (MHz)	2400-5950	2400-7125	700-8000	210-728

RF PRODUCT(Antenna)

Multilayer

SLDA Series 2.45GHz

						
Center Freq. (GHz)	2.4~2.8	2.51~2.54	2.64	2.47	3.01	2.66
Band Width (MHz)	≥100	≥200	≥200	≥200	≥200	≥200
Peak Gain (dBi)	0.5~2.5	2.5	2.6	2.7	2.0	3.0

RF PRODUCT

Wire Wound Chip Balun Transformer

BW21S Series TV tuner

		
Freq. Range (MHz)	BW21S 45-2150	BW21C 13.56
Port Impedance (Ω)	50/50-75/75	25/25

BW43S Series

	
Inductance @50MHz (uH)	BW43S 1.00-1.25
Port Impedance (Ω)	50/50

